

# INDUSTRIAL FITTINGS - couplings

## HAMMER LUG system



**Material:** A105 carbon steel  
(for types 100 ÷ 400)  
AISI 4130steel  
(for 600 ÷ 2202 types)

**Working press.:** From 69 bar up to 1378 bar  
(depending on type)

The HAMMER LUG couplings are designed for quick connection of flexible hose assemblies and pipelines. Widely used in transfer applications for air, oil, water, drilling fluid, gas and other substances. Available in a variety of options (threaded, butt weld) in diameters from 1" up to 8". Available with DNV Type Approval. To find out more about HAMMER LUG offer, please contact Sales Department of TUBES INTERNATIONAL®.

**Note: Connection of different figures is forbidden!**



picture	code	description	size	characteristics
	<b>Fig. 100</b>			
	HL-FIG0100KG-050	(male, female + wing nut)	2"	General purpose low pressure coupling. Widely used to transfer air, water, oil and gas. Colour: yellow / black. Pressure: 1000 PSI (69 bar). Material: carbon steel. Connection: NPT female thread. Seal: metal / metal (cone).
	HL-FIG0100DG-050	female	2"	
	HL-FIG0100MG-050	male	2"	
	HL-FIG0100NG-050	wing nut	2"	
	HL-FIG0100KG-075	(male, female + wing nut)	3"	
	HL-FIG0100DG-075	female	3"	
	HL-FIG0100MG-075	male	3"	
	HL-FIG0100NG-075	wing nut	3"	
	HL-FIG0100KG-100	(male, female + wing nut)	4"	
	HL-FIG0100DG-100	female	4"	
	HL-FIG0100MG-100	male	4"	
	HL-FIG0100NG-100	wing nut	4"	
	HL-FIG0100KG-150	(male, female + wing nut)	6"	
	HL-FIG0100DG-150	female	6"	
HL-FIG0100MG-150	male	6"		
HL-FIG0100NG-150	wing nut	6"		