

INDUSTRIAL FITTINGS - valves

Gate valves



Gate valve 2029 type

Body material: AISI 316 steel
Gate material: AISI 316 steel
Knob material: Aluminium
Stem seal: PTFE
Connection: BSP female thread
Working temp.: From -20°C up to +200°C

A general purpose gate valve designed for industrial installations. The valve can be used to control or throttle flow. Working pressure depends on working temperature.

code	DN [mm]	thread size [inch]	working pressure [bar]
HT-2029-15	15	1/2	10
HT-2029-20	20	3/4	10
HT-2029-25	25	1	10
HT-2029-32	32	1.1/4	10
HT-2029-40	40	1.1/2	10
HT-2029-50	50	2	10
HT-2029-65	65	2.1/2	10
HT-2029-80	80	3	10



Gate valve 560 type

Body material: Brass
Gate material: Brass
Handle material: Carbon steel
Connection: BSP female thread (NPT available)
Working temp.: From -20°C up to +90°C

A lever gate valve allows quick opening and closing of the fluid flow. Two horizontally pivoted discs design ensures perfect valve tightness. Widely used in agriculture, septic tank trucks, industry. Meets the requirements of Directive 97/23/CE (PED). Working pressure depends on working temperature.

code	thread size [inch]	flow diameter [mm]	build-in length [mm]	working pressure [bar]	weight [kg]
RV-0560-050	2	49	75	16	1.77
RV-0560-065	2.1/2	59	80	16	3.12
RV-0560-075	3	70	86	10	4.08
RV-0560-100	4	93	92	10	6.08