

Hose cutting machines




HY-9085-01-01

KNIFE CUT 4-30 BT

A pneumatic cutting machine intended to cut rubber and thermoplastic hoses with textile braid and plastic hoses with external diameter ranging from 4 mm up to 30 mm. Equipped with tools for cutting single and double hoses. Operated with a foot pedal. Ensures clean and straight cut.

- maximum hose outside diameter: 30 mm,
- pneumatically operated 6 bar,
- cutting power 1683 N,
- weight: 14 kg.



HY-9006-01-00

MINI CUT 5-50

A cutting machine developed to cut hydraulic hoses with 1 or 2 braids of up to 2" in diameter and with 4 braids of up to 1.1/4" in diameter. Designed for workshops and service vans.

- maximum hose outside diameter: 80 mm,
- operated by: three-phase 3 kW motor,
12/24 V 1.1 kW motor (battery powered),
- speed of revolutions: 2880 r.p.m.,
- standard cutting blade: Ø 300x3x50 mm - smooth (a toothed blade can also be used),
- weight: 45 kg,
- can be connected to external fume removal system (Ø 63 mm).



HY-9009-00-00

MAXI CUT 5-60 OT

A cutting machine developed to cut hydraulic hoses with 1, 2 or 4 braids of up to 2" in diameter.

Designed for series production of hydraulic hose assemblies.

- maximum hose outside diameter: 80 mm,
- operated by: three-phase 5.5 kW motor,
- pneumatically operated min. 6 bar,
- speed of revolutions: 2850 r.p.m.,
- standard cutting blade: Ø 400x4x50 mm - smooth (a toothed blade can also be used),
- hose is pneumatically pushed against the blade,
- three-grade cutting speed,
- weight: 140 kg,
- can be connected to external fume removal system (Ø 100 mm).



HY-9010-00-00

POWER CUT 5-75 OT

A cutting machine developed to cut hydraulic hoses with 1 or 2 braids of up to 3" in diameter and with 6 braids of up to 2" in diameter. Designed for series production of hydraulic hose assemblies.

- maximum hose outside diameter: 90 mm,
- operated by: three-phase 7.5 kW motor,
- pneumatically operated min. 6 bar,
- speed of revolutions: 2850 r.p.m.,
- standard cutting blade: Ø 520x4x38 mm - smooth, (a toothed blade can be also used),
- hose is pneumatically pushed against the blade,
- adjustable cutting speed,
- weight: 210 kg,
- can be connected to external fume removal system (Ø 100 mm).