Hydraulic ball valves

BK3L BSP / NPT (1/8” ÷ 1”)

Three-way hydraulic ball valves,
BSP / NPT thread, high quality (PISTER)

Material: body, ball, stem – galvanised steel
Seals: ball - POM
stem - NBR
Temp. working: POM - (from -40°C to +100°C)
NBR - (from -20°C to +100°C)

Three-way L-type ball valves with BSP or NPT female threads, designed for high-pressure hydraulic systems.

index	DN [mm]	size thread D [inch]	pressure working [bar]	length valve L [mm]	weight [kg]
HZ-BK3L-G-02	4	1/8 BSP	400	69	0,40
HZ-BK3L-G-04	6	1/4 BSP	400	69	0,40
HZ-BK3L-G-06	10	3/8 BSP	400	73	0,55
HZ-BK3L-G-08	13	1/2 BSP	350	85	0,70
HZ-BK3L-G-12	20	3/4 BSP	350	96	1,55
HZ-BK3L-N-02	4	1/8 NPT	400	69	0,40
HZ-BK3L-N-04	6	1/4 NPT	400	69	0,40
HZ-BK3L-N-06	10	3/8 NPT	400	73	0,55
HZ-BK3L-N-08	13	1/2 NPT	350	92	0,70
HZ-BK3L-N-12	20	3/4 NPT	350	97	1,55
HZ-BK3L-N-16	25	1 NPT	350	113	2,10

SK3L BSP / NPT (3/4” ÷ 2”)

Three-way hydraulic ball valves,
BSP / NPT thread, high quality (PISTER)

Material: body, ball, stem – galvanised steel
Seals: ball - POM
stem - NBR
Temp. working: POM - (from -40°C to +100°C)
NBR - (from -20°C to +100°C)

Three-way L-type ball valves with BSP or NPT female threads, designed for high-pressure hydraulic systems.

index	DN [mm]	size thread D [inch]	pressure working [bar]	length valve L [mm]	weight [kg]
HZ-SK3L-G-12	20	3/4 BSP	350	96	1,55
HZ-SK3L-G-16	25	1 BSP	350	113	2,10
HZ-SK3L-G-20	32	1.1/4 BSP	350	110	3,40
HZ-SK3L-G-24	40	1.1/2 BSP	350	120	4,20
HZ-SK3L-G-32	50	2 BSP	350	140	6,10
HZ-SK3L-N-20	32	1.1/4 NPT	350	115	3,40
HZ-SK3L-N-24	40	1.1/2 NPT	350	135	4,20
HZ-SK3L-N-32	50	2 NPT	350	140	6,20