



# CLEANING AND WASHING - low pressure

## Adjustable nozzles

### NiTO adjustable nozzles

picture	code	connection	material	description
	NT-53750A3	1/2" NiTO plug	chromium plated brass	NiTO adjustable nozzles, adjusted by turning. Designed for 1/2" and 3/4" hoses. Connection: NiTO quick release plug (see section „INDUSTRIAL FITTINGS - quick release couplings“), BSP thread and hose tail. Working press.: up to 25 bar.
	NT-63750A3	3/4" NiTO plug	chromium plated brass	
	NT-20300A9	3/4" female thread	nickel-plated brass	
	NT-20000A4	15/20 mm hose tail	brass	
	NT-57140A1	1/2" NiTO plug	chromium plated brass, plastic	

### HANDIFIGHTER adjustable nozzles

picture	code	connection	description
	IN-59481-020 (short)	3/4" female thread	Industrial water nozzle with adjustable outlet. EPDM rubber ring protects against mechanical damage. Material: brass. Cover: highly durable plastic Nozzle: 7 mm. Working press.: 16 bar. Flow rate: 75 l/min (6 bar).\
	IN-59481-120 (short)	19 (20) mm hose tail	
	IN-59481-220 (long)	3/4" female thread	
	IN-59481-225 (long)	1" male thread	
	IN-59482-020 (short)	3/4" male thread	Industrial water nozzle with adjustable outlet. EPDM rubber ring protects against mechanical damage. Material: brass. Cover: highly durable plastic Nozzle: 10 mm. Working press.: 16 bar. Flow rate: 150 l/min (6 bar).
	IN-59482-125 (short)	25 mm hose tail	
	IN-59482-220 (long)	3/4" female thread	
	IN-59482-225 (long)	1" male thread	