



Hoses for cooling systems



DERBY RADIATOR

Hose for cooling systems DIN 73411-79

Inner layer: Black EPDM rubber
Reinforcement: synthetic cord
Outer layer: Black EPDM rubber
Operating temp: -40°C to +120°C

Delivery hose designed for hot water mixed with anti-freeze. Used in cooling and heating systems, for pumps in engines and machinery. Inner layer resistant to heat and coolants. Outer layer resistant to heat and ageing. Manufactured in accordance with DIN 73411:79.

index	internal diameter [mm]	external diameter [mm]	wall thickness [mm]	working pressure [bar]	Bursting pressure [bar]	mass [kg/m]	Roll length [m]
IV-RADIATOR-008	8	15	3,5	4	12	0,15	60 / 120
IV-RADIATOR-010	10	18	4	4	12	0,19	60 / 120
IV-RADIATOR-012	12	19	3,5	4	12	0,19	60 / 120
IV-RADIATOR-013	13	20	3,5	4	12	0,21	60 / 120
IV-RADIATOR-015	15	22	3,5	4	12	0,23	60 / 120
IV-RADIATOR-016	16	23	3,5	4	12	0,22	60 / 120
IV-RADIATOR-018	18	25	3,5	4	12	0,27	60 / 120
IV-RADIATOR-019	19	28	4,5	4	12	0,37	60 / 120
IV-RADIATOR-020	20	27	3,5	4	12	0,30	60 / 120
IV-RADIATOR-022	22	29	3,5	4	12	0,33	60 / 120
IV-RADIATOR-025	25	32	3,5	4	12	0,36	60 / 120
IV-RADIATOR-028	28	36	4	4	12	0,44	60 / 120
IV-RADIATOR-030	30	38	4	4	12	0,47	60 / 120
IV-RADIATOR-032	32	40	4	4	12	0,49	60 / 120
IV-RADIATOR-035	35	43	4	4	12	0,54	60 / 120
IV-RADIATOR-038	38	48	5	4	12	0,78	60 / 120
IV-RADIATOR-040	40	50	5	4	12	0,81	60 / 120
IV-RADIATOR-042	42	52	5	4	12	0,85	60 / 120
IV-RADIATOR-045	45	55	5	4	12	0,90	60 / 120
IV-RADIATOR-048	48	58	5	4	12	0,96	60 / 120
IV-RADIATOR-050	50	60	5	3	9	0,99	60 / 120
IV-RADIATOR-055	55	65	5	3	9	1,08	60 / 120
IV-RADIATOR-060	60	70	5	3	9	1,17	60 / 120
IV-RADIATOR-065	65	75	5	3	9	1,26	60 / 120
IV-RADIATOR-070	70	80	5	3	9	1,35	60 / 120
IV-RADIATOR-075	75	85	5	3	9	1,45	60 / 120
IV-RADIATOR-080	80	91,5	5,75	3	9	1,73	60 / 120
IV-RADIATOR-100	100	112,5	6,25	2	6	2,37	60 / 120
IV-RADIATOR-110	110	122	6	2	6	2,44	60 / 120
IV-RADIATOR-114	114	126	6	2	6	2,52	60

Note: indexes highlighted in colour - most commonly used

DERBY RADIATOR hose DN16 with brass end (NT-2664NA4) with 1/2" BSPT male thread clamped with galvanised steel worm band.

