











## JETON coolant system

### JETON coolant line components - continuation of table

drawing	description	index			
		1/4" system	3/8" system	1/2" system	3/4" system
	Side nozzle	JT-62422	-	JT-64622	-
	90° flat jet nozzle with holes	JT-82226 (6x2.3 mm)	-	JT-84446 (8x4.2 mm)	-
	Flat slot nozzle	JT-82017 (7x1.3 mm)	-	-	-
	Flat slot nozzle	JT-82027 (25x1.7 mm)	JT-83037 (32.1x3.2 mm)	JT-84047 (32x4.5 mm) JT-84050 (47.3x4.4 mm) JT-84052 (61x3.5 mm)	JT-86067 (77.3x4.8 mm)
	Flat nozzle with adjustable hole head	JT-82228 (16 holes 1 mm) JT-82229 (16 holes 1.5 mm)	-	JT-84447 (20 holes 1.8 mm)	-
	Connection with male thread	JT-82025A (1/8" NPT) JT-82025 (1/8" BSPT) JT-82026A (1/4" NPT) JT-82026 (1/4" BSPT)	JT-83035A (3/8" NPT) JT-83035 (3/8" BSPT) JT-83036A (1/2" NPT) JT-83036 (1/2" BSPT)	JT-84046A (3/8" NPT) JT-84046 (3/8" BSPT) JT-84045A (1/2" NPT) JT-84045 (1/2" BSPT)	JT-86064A (3/4" NPT) JT-86064 (3/4" BSPT)
	Transition from 1/4" socket to 1/8" NPT GW	JT-82012	-	-	-
	Two-socket switch	JT-82011	JT-83011	JT-84011	JT-86011

