

CLEANING AND WASHING - high pressure

High pressure MTM water spray guns

picture	code	connection	description
	MH-100465	3/8" female	„SG35" spray gun with KC35 type quick release coupling socket. Working press.: up to 310 bar. Flow rate: 45 l/min. Working temp.: up to +160°C.
	MH-100466	3/8" female - swivel	
	MH-100469	3/8" female	„SG35" spray gun with BC35 type quick release coupling socket. Working press.: up to 310 bar. Flow rate: 45 l/min. Working temp.: up to +160°C.
	MH-100470	3/8" female - swivel	
	MH-100398	M22x1.5 male	„SG35" spray gun with M22x1.5 male outlet. Working press.: up to 310 bar. Flow rate: 45 l/min. Working temp.: up to +160°C.
	MH-100399	M22x1.5 male - swivel	
	MH-100400	3/8" female	„SG35" spray gun with MT8 lance with M22x1.5 female outlet. Lance made of acid-resistant steel. Working press.: up to 310 bar. Flow rate: 45 l/min. Working temp.: up to +160°C. * - lance of zinc-plated steel.
	MH-100401	3/8" male	
	MH-100402	M22x1.5	
	MH-100403*	3/8" female	
	MH-100404*	3/8" female	
	MH-100405*	M22x1.5 male	
	MH-100406	3/8" female - swivel	
MH-100407*	3/8" female - swivel		
	MH-100024	3/8" female	„AURA" spray gun with MT5 lance with M22x1.5 outlet. Lance made of acid-resistant steel. Working press.: up to 180 bar. Flow rate: 30 l/min. Working temp.: up to +160°C. * - lance of zinc-plated steel.
	MH-100168	3/8" male	
	MH-100169	M22x1.5 male	
	MH-100025*	3/8" female	
	MH-100171*	3/8" male	