

INDUSTRIAL FITTINGS - fittings, connectors

Brass connectors - MU type

Working press::Up to 12 bar

Working temp.:From -20°C up to +100°C

Nipple BSP male (internal cone)



code	thread size [inch]	thread size [inch]	spanner size [mm]
MU-4201	1/8	1/8	14
MU-4202	1/8	1/4	17
MU-4203	1/4	1/4	17
MU-4204	1/4	3/8	19
MU-4208	1/4	1/2	24
MU-4205	3/8	3/8	19
MU-4206	3/8	1/2	24
MU-4213	3/8	3/4	32
MU-4207	1/2	1/2	24
MU-4209	1/2	3/4	32
MU-4215	1/2	1	36
MU-4211	3/4	3/4	32
MU-4210	3/4	1	36
MU-4216	1	1	36

Reduction adapter BSP female / male



code	thread size [inch]	thread size [inch]	spanner size [mm]
MU-4251	1/4	1/8	17
MU-4256	3/8	1/8	19
MU-4252	3/8	1/4	19
MU-4257	1/2	1/8	24
MU-4254	1/2	1/4	24
MU-4253	1/2	3/8	21
MU-4258	3/4	3/8	32
MU-4255	3/4	1/2	32
MU-4259	1	1/2	36
MU-4260	1	3/4	36

90° elbow BSP female



code	thread size [inch]
MU-1142	1/8
MU-1143	1/4
MU-1144	3/8
MU-1145	1/2
MU-1146	3/4
MU-1147	1

"T" Tee connection BSP female



code	thread size [inch]
MU-1172	1/8
MU-1173	1/4
MU-1174	3/8
MU-1175	1/2
MU-1176	3/4
MU-1177	1

"Y" Tee connection BSP female



code	thread size [inch]
MU-1190	3/8
MU-1191	1/2

Cross BSP female



code	thread size [inch]
MU-1195	3/8
MU-1198	1/2

* - versions with EUROSTANDARD DN 5, DN7.2 couplers available as well