Push-in couplings series C

Material: Nickel-plated brass
Working pressure: Up to 18 bar

Push-in couplings designed for connecting soft plastic hoses. The connection is made by pushing the hose onto the tail and clamping it by tightening the nut.

Straight connector, tapered male thread



C1

index	hose diameter outer / inner [mm]	thread size (BSPT)
MW-2301017	5/3	1/8"
MW-2301001	6/4	1/8"
MW-2301002	6/4	1/4"
MW-2301003	8/6	1/8"
MW-2301004	8/6	1/4"
MW-2301005	8/6	3/8"
MW-2301020	10/8	1/8"
MW-2301006	10/8	1/4"
MW-2301007	10/8	3/8"
MW-2301008	10/8	1/2"
MW-2301009	12/10	3/8"
MW-2301010	12/10	1/2"
MW-2301015	15/12,5	1/2"

Straight connector, male thread, O-ring seal, NBR



C1/Z

index	hose diameter outer / inner [mm]	thread size (BSP, metric)
MW-2351001	4/2	M5
MW-2351002	6/4	M5
MW-2351003	6/4	1/8"
MW-2351004	6/4	1/4"
MW-2351005	8/6	1/8"
MW-2351006	8/6	1/4"
MW-2351007	8/6	3/8"
MW-2351008	10/8	1/4"
MW-2351009	10/8	3/8"
MW-2351010	10/8	1/2"
MW-2351011	12/10	3/8"
MW-2351012	12/10	1/2"

Straight connector, male thread



C1/C

index	hose diameter outer / inner [mm]	thread size (BSP, metric)
MW-2356001	5/3	M5
MW-2356002	6/4	M6
MW-2356003	6/4	M12x1,5
MW-2356004	6/4	3/8"
MW-2356005	8/6	M12x1,5

Straight connector, female thread



C2

index	hose diameter outer / inner [mm]	thread size (BSP, metric)
MW-2302001	6/4	1/8"
MW-2302002	6/4	1/4"
MW-2302012	6/4	3/8"
MW-2302003	8/6	1/8"
MW-2302004	8/6	1/4"
MW-2302005	8/6	3/8"
MW-2302006	10/8	1/4"
MW-2302007	10/8	3/8"
MW-2302008	10/8	1/2"