




INDUSTRIAL FITTINGS - quick release couplings



NITTO KOHKI couplings

Plug with BSPT male thread 	code (brass)	code (carbon steel)	code (AISI 304)	thread size [inch]	Lp [mm]	A [mm]	Bp [mm]	Bd [mm]
	NK-20PM-B	NK-20PM-S	NK-20PM-SS	1/4	41	13	7.5	7.5
	NK-30PM-B	NK-30PM-S	NK-30PM-SS	3/8	42	14	7.5	7.5
	NK-40PM-B	NK-40PM-S	NK-40PM-SS	1/2	46	16	12	7.5
	NK-400PM-B	NK-400PM-S	NK-400PM-SS	1/2	50	16	13	13
	NK-600PM-B	NK-600PM-S	NK-600PM-SS	3/4	55	18	19	13
	NK-800PM-B	NK-800PM-S	NK-800PM-SS	1	63	22	22	13

Socket with BSPT female thread 	code (brass)	code (carbon steel)	code (AISI 304)	thread size [inch]	Ls [mm]	A [mm]	D [mm]
	NK-20SF-B	NK-20SF-S	NK-20SF-SS	1/4	49.5	13	26.5
	NK-30SF-B	NK-30SF-S	NK-30SF-SS	3/8	50.5	14	26.5
	NK-40SF-B	NK-40SF-S	NK-40SF-SS	1/2	52.5	15	26.5
	NK-400SF-B	NK-400SF-S	NK-400SF-SS	1/2	57	15	35
	NK-600SF-B	NK-600SF-S	NK-600SF-SS	3/4	61	17	35
	NK-800SF-B	NK-800SF-S	NK-800SF-SS	1	68	22	35

Plug with BSPT female 	code (brass)	code (carbon steel)	code (AISI 304)	thread size [inch]	Lp [mm]	A [mm]	C [mm]	Bd [mm]
	NK-20PF-B	NK-20PF-S	NK-20PF-SS	1/4	36	13	20	7.5
	NK-30PF-B	NK-30PF-S	NK-30PF-SS	3/8	37	14	20	7.5
	NK-40PF-B	NK-40PF-S	NK-40PF-SS	1/2	38	15	20	7.5
	NK-400PF-B	NK-400PF-S	NK-400PF-SS	1/2	41	15	23	13
	NK-600PF-B	NK-600PF-S	NK-600PF-SS	3/4	45	17	23	13
	NK-800PF-B	NK-800PF-S	NK-800PF-SS	1	54	22	23	13

HI CUPLA - divider system

NK-200L  NK-200S 	code	connection		description
		inlet (plug)	outlet (socket)	
NK-200L	1/2"	1 x 1/2" 4 x 1/4"	HI CUPLA divider system (version of chromium-plated steel with caps). Body material: aluminium. Seal: NBR. Working press: 15 bar. Working temp.: from -5°C up to +60°C	
NK-200S	1/2"	1 x 1/2" 4 x 1/4"		