




# INDUSTRIAL FITTINGS - valves

## Stainless steel hygienic valves

| picture                                                                                                                                      | code          | DN  | flow diameter [mm] | build-in length [mm] | plate diameter [mm] | weight [kg] |
|----------------------------------------------------------------------------------------------------------------------------------------------|---------------|-----|--------------------|----------------------|---------------------|-------------|
| Valve acc. to. DIN 32676-A,<br>TRICLOVER end connection<br> | NM-DIN-CC-010 | 10  | 10                 | 76                   | 34                  | 0.60        |
|                                                                                                                                              | NM-DIN-CC-015 | 15  | 16                 | 76                   | 34                  | 0.60        |
|                                                                                                                                              | NM-DIN-CC-020 | 20  | 20                 | 76                   | 34                  | 0.60        |
|                                                                                                                                              | NM-DIN-CC-025 | 25  | 26                 | 64                   | 50.5                | 1.50        |
|                                                                                                                                              | NM-DIN-CC-032 | 32  | 32                 | 72                   | 50.5                | 1.50        |
|                                                                                                                                              | NM-DIN-CC-040 | 40  | 38                 | 72                   | 50.5                | 1.70        |
|                                                                                                                                              | NM-DIN-CC-050 | 50  | 50                 | 72                   | 64                  | 1.90        |
|                                                                                                                                              | NM-DIN-CC-065 | 65  | 66                 | 76                   | 91                  | 2.40        |
|                                                                                                                                              | NM-DIN-CC-080 | 80  | 81                 | 100                  | 106                 | 4.40        |
| NM-DIN-CC-100                                                                                                                                | 100           | 100 | 104                | 119                  | 5.20                |             |

| picture                                                                                                                                  | code          | DN  | flow diameter [mm] | build-in length [mm] | pipe O.D. [mm] | weight [kg] |
|------------------------------------------------------------------------------------------------------------------------------------------|---------------|-----|--------------------|----------------------|----------------|-------------|
| Valve according to ISO,<br>welding end connection<br> | NM-ISO-SS-025 | 25  | 28.5               | 40                   | 33.7           | 1.3         |
|                                                                                                                                          | NM-ISO-SS-032 | 32  | 37.2               | 42                   | 42.4           | 1.4         |
|                                                                                                                                          | NM-ISO-SS-040 | 40  | 43.1               | 50                   | 48.3           | 1.5         |
|                                                                                                                                          | NM-ISO-SS-050 | 50  | 55.1               | 50                   | 60.3           | 1.8         |
|                                                                                                                                          | NM-ISO-SS-065 | 65  | 70.9               | 50                   | 76.1           | 2.2         |
|                                                                                                                                          | NM-ISO-SS-080 | 80  | 83.7               | 60                   | 88.9           | 4.0         |
|                                                                                                                                          | NM-ISO-SS-100 | 100 | 109.1              | 64                   | 114.3          | 4.8         |

| picture                                                                                                                           | code           | DN  | flow diameter [mm] | build-in length [mm] | pipe O.D. [mm] | weight [kg] |
|-----------------------------------------------------------------------------------------------------------------------------------|----------------|-----|--------------------|----------------------|----------------|-------------|
| Valve according to ISO,<br>welding flanges<br> | NM-ISO-ZFA-025 | 25  | 29.7               | 90                   | 33.7           | 1.3         |
|                                                                                                                                   | NM-ISO-ZFA-032 | 32  | 38.4               | 90                   | 42.4           | 1.4         |
|                                                                                                                                   | NM-ISO-ZFA-040 | 40  | 44.3               | 100                  | 48.3           | 1.5         |
|                                                                                                                                   | NM-ISO-ZFA-050 | 50  | 56.3               | 100                  | 60.3           | 1.8         |
|                                                                                                                                   | NM-ISO-ZFA-065 | 65  | 71.5               | 100                  | 76.1           | 2.2         |
|                                                                                                                                   | NM-ISO-ZFA-080 | 80  | 84.3               | 136                  | 88.9           | 4.0         |
|                                                                                                                                   | NM-ISO-ZFA-100 | 100 | 109.1              | 136                  | 114.3          | 4.8         |