NiTO brass hose ends and connectors

Type B hose ends

Popular hose ends for water, air and other media

Material: brass
Working pressure: up to 25 bar
Working temperature: up to +80°C

Brass hose ends with parallel male BSP thread and tapered BSPT thread with a straight (flat) end. Sealing of BSPT tapered-thread ends is done on the thread using a suitable sealant (PTFE tape, liquid sealant). Sealing of parallel BSP-thread ends should be done on the thread (as for BSPT) or by using a flat gasket. Intended for water, air and other media. Used in particular for water from the mains supply: in horticulture, agriculture, industry, connecting drums to hoses and water guns, and all other applications.

Type B hose end for hose with male BSP thread

index	thread size [inch]	diameter hose
NT-2760AA4	1/8”	1/8” (3.5 mm)
NT-2764AA4	1/8”	1/4” (6.5 mm)
NT-2766AA4	1/8”	3/8” (10.2 mm)
NT-2760BA4	1/4”	1/4” (6.5 mm)
NT-2768BA4	1/4”	5/16” (8.5 mm)
NT-2764BA4	1/4”	3/8” (10.2 mm)
NT-2766BA4	1/4”	1/2” (13.5 mm)
NT-2764CA4	3/8”	1/4” (6.5 mm)
NT-2760CA4	3/8”	3/8” (10.2 mm)
NT-2766CA4	3/8”	1/2” (13.5 mm)
NT-2764DA4	1/2”	1/4” (6.5 mm)
NT-2768DA4	1/2”	5/16” (8.5 mm)
NT-2766DA4	1/2”	3/8” (10.2 mm)
NT-2760DA4	1/2”	1/2” (13.5 mm)
NT-2764NA4	1/2”	5/8” (16.5 mm)
NT-2766NA4	1/2”	3/4” (19.5 mm)
NT-2766EA4	3/4”	1/2” (13.5 mm)
NT-2760EA4	3/4”	3/4” (19.5 mm)
NT-2760FA4	1”	1” (26 mm)
NT-2760GA4	1.1/4”	1.1/4” (32 mm)
NT-2760HA4	1.1/2”	1.1/2” (39 mm)
NT-2760IA4	2”	2” (51 mm)

Hose connector

index	hose diameter [inch]
NT-15020A4	1/2”
NT-15030A4	3/4”
NT-15040A4	1”

Type B hose end for hose with male BSPT thread

index	thread size [inch]	diameter hose
NT-2660AA4	1/8”	1/8” (3.5 mm)
NT-2664AA4	1/8”	1/4” (6.5 mm)
NT-2666AA4	1/8”	3/8” (10.2 mm)
NT-2660BA4	1/4”	1/4” (6.5 mm)
NT-2668BA4	1/4”	5/16” (8.5 mm)
NT-2664BA4	1/4”	3/8” (10.2 mm)
NT-2666BA4	1/4”	1/2” (13.5 mm)
NT-2664CA4	3/8”	1/4” (6.5 mm)
NT-2660CA4	3/8”	3/8” (10.2 mm)
NT-2666CA4	3/8”	1/2” (13.5 mm)
NT-2664EA4	3/8”	3/4” (19.5 mm)
NT-2664DA4	1/2”	1/4” (6.5 mm)
NT-2668DA4	1/2”	5/16” (8.5 mm)
NT-2666DA4	1/2”	3/8” (10.2 mm)
NT-2660DA4	1/2”	1/2” (13.5 mm)
NT-2664NA4	1/2”	5/8” (16.5 mm)
NT-2666NA4	1/2”	3/4” (19.5 mm)
NT-2666EA4	3/4”	1/2” (13.5 mm)
NT-2660EA4	3/4”	3/4” (19.5 mm)
NT-2660FA4	1”	1” (26 mm)

ARMORVIN PRESS PU DN20 hose with a brass hose end (NT-2760EA4) with a 3/4” BSP male thread, fitted with a worm-drive clamp.