






INDUSTRIAL FITTINGS - quick release couplings

NiTO SC with a safety lock - couplings for water




Material: Chrome-plated brass
Working press.: Up to 25 bar
Working temp.: Up to +150°C
Sealing: Viton

Quick release couplings NiTO SC (Safety Coupling) are used for hot water applications (above +60°C), where an operator has a direct contact with couplings or when couplings are frequently disconnected (e.g. gun assembly). Due to their unique construction the couplings interlock when under pressure and disconnect only if the water supply is shut off. Particularly recommended for hot water guns connection.

| picture | description | code | size |
|---|---|------------|--------|
|  | Socket with hose tail (B) (for HEAVY DUTY and NiTO II gun) | NT-6150SA8 | B-3/4" |
|  | | NT-6151SA8 | B-1/2" |
|  | Plug with male thread (C) (for HEAVY DUTY gun) | NT-61640A8 | C-1/2" |
|  | Plug with male thread (C) (for NiTO II gun) | NT-61650A3 | C-3/4" |
| | Plug with hose tail (B) | NT-61660A3 | B-1/2" |
| | | NT-61670A3 | B-3/4" |

NiTO CLICK 1/2" - 3/4" system - couplings for water



Material: Chrome-plated brass (matt - satin)
Working press.: Up to 25 bar
Working temp.: Up to +150°C
Sealing: NBR - not suitable for oil and petrol (Viton seal as an option). EPDM O-ring for a valve.

NiTO CLICK quick release couplings are manufactured according to the profile of popular quick release plastic couplings with the same sealing type - O-ring on the plug external surface. They are fully compatible with plastic quick release couplings used in gardening, public facilities and industry. Made of metal - for long service life.