

INDUSTRIAL FITTINGS - couplings

Lever couplings ANFOR



Material: Galvanized steel
Seal: NR-SBR
Working press.: 19 bar - size 60 mm
 16 bar - size 80 mm
 14 bar - size 100 mm
 13 bar - size 120 mm
 12 bar - size 150 mm
 6 bar - size 200 mm
 5 bar - sizes 250, 300, 400 mm
Working temp.: From -20°C up to +50°C

ANFOR couplings (pipes and fittings) are widely used in farming, gardening, industry, construction, road and tunnel building, groundwater drainage, sewage treatment plants, wastewater disposal and environmental engineering. Coupling design allows angular deflection of the connected coupling (max. 22° in small sizes, 16° in big sizes). Available in a wide pipe diameter range (60, 80, 100, 120, 150, 200, 250, 300, 400 mm) and as a version with three hooks (for higher working pressure).

Plug end cap	
A.5B	
code	size
OM-A5B-060	60
OM-A5B-080	80
OM-A5B-100	100
OM-A5B-120	120
OM-A5B-150	150
OM-A5B-200	200
OM-A5B-250	250
OM-A5B-300	300

Socket end cap	
A.6B	
code	size
OM-A6B-060	60
OM-A6B-080	80
OM-A6B-100	100
OM-A6B-120	120
OM-A6B-150	150
OM-A6B-200	200
OM-A6B-250	250
OM-A6B-300	300

Socket with hose tail		
A.7		
code	size	hose I.D. [mm]
OM-A7-060-060	60	60
OM-A7-080-080	80	80
OM-A7-100-100	100	100
OM-A7-120-120	120	120
OM-A7-150-150	150	150
OM-A7-200-200	200	200
OM-A7-250-250	250	250
OM-A7-300-300	300	300
OM-A7-400-400	400	400

Plug with hose tail		
A.8		
code	size	hose I.D. [mm]
OM-A8-060-060	60	60
OM-A8-080-080	80	80
OM-A8-100-100	100	100
OM-A8-120-120	120	120
OM-A8-150-150	150	150
OM-A8-200-200	200	200
OM-A8-250-250	250	250
OM-A8-300-300	300	300
OM-A8-400-400	400	400