

# INDUSTRIAL FITTINGS - couplings

## Lever couplings ANFOR



**Material:** Galvanized steel  
**Seal:** NR-SBR  
**Working press.:** 19 bar - size 60 mm  
 16 bar - size 80 mm  
 14 bar - size 100 mm  
 13 bar - size 120 mm  
 12 bar - size 150 mm  
 6 bar - size 200 mm  
 5 bar - sizes 250, 300, 400 mm  
**Working temp.:** From -20°C up to +50°C

ANFOR couplings (pipes and fittings) are widely used in farming, gardening, industry, construction, road and tunnel building, groundwater drainage, sewage treatment plants, wastewater disposal and environmental engineering. Coupling design allows angular deflection of the connected coupling (max. 22° in small sizes, 16° in big sizes). Available in a wide pipe diameter range (60, 80, 100, 120, 150, 200, 250, 300, 400 mm) and as a version with three hooks (for higher working pressure).

Plug end cap	
<b>A.5B</b>	
code	size
OM-A5B-060-000	60
OM-A5B-080-000	80
OM-A5B-100-000	100
OM-A5B-120-000	120
OM-A5B-150-000	150
OM-A5B-200-000	200
OM-A5B-250-000	250
OM-A5B-300-000	300

Socket end cap	
<b>A.6B</b>	
code	size
OM-A6B-060-000	60
OM-A6B-080-000	80
OM-A6B-100-000	100
OM-A6B-120-000	120
OM-A6B-150-000	150
OM-A6B-200-000	200
OM-A6B-250-000	250
OM-A6B-300-000	300

Socket with hose tail		
<b>A.7</b>		
code	size	hose I.D. [mm]
OM-A7-060-060	60	60
OM-A7-080-080	80	80
OM-A7-100-100	100	100
OM-A7-120-120	120	120
OM-A7-150-150	150	150
OM-A7-200-200	200	200
OM-A7-250-250	250	250
OM-A7-300-300	300	300
OM-A7-400-400	400	400

Plug with hose tail		
<b>A.8</b>		
code	size	hose I.D. [mm]
OM-A8-060-060	60	60
OM-A8-080-080	80	80
OM-A8-100-100	100	100
OM-A8-120-120	120	120
OM-A8-150-150	150	150
OM-A8-200-200	200	200
OM-A8-250-250	250	250
OM-A8-300-300	300	300
OM-A8-400-400	400	400