

# INDUSTRIAL FITTINGS - couplings

## Lever couplings FERRARI



**Material:** Galvanized steel  
**Seal:** NR-SBR  
**Working press.:** 10 bar - sizes 48, 60 mm  
                   9 bar - size 80 mm  
                   8 bar - size 100 mm  
                   7 bar - size 120 mm  
                   6 bar - size 150 mm  
**Working temp.:** From -20°C up to +50°C

FERRARI couplings (pipes and fittings) are widely used in farming, gardening, industry, construction, road and tunnel building, groundwater drainage, sewage treatment plants, wastewater disposal and environmental engineering. Coupling design allows angular deflection of the connected coupling (max. 26° in small sizes, 20° in big sizes). Available in a wide pipe diameter range (48, 60, 80, 100, 120, 150 mm), as a version with three hooks (for higher working pressure) and made of AISI 304 steel.

Plug end cap	
<b>F.5B</b>	
code	size
OM-F5B-048-000	48
OM-F5B-060-000	60
OM-F5B-080-000	80
OM-F5B-100-000	100
OM-F5B-120-000	120
OM-F5B-150-000	150

Socket end cap	
<b>F.6B</b>	
code	size
OM-F6B-048-000	48
OM-F6B-060-000	60
OM-F6B-080-000	80
OM-F6B-100-000	100
OM-F6B-120-000	120
OM-F6B-150-000	150

Reducing socket with hose tail		
<b>F.10</b>		
code	size	hose I.D. [mm]
OM-F10-060-050	60	50
OM-F10-060-063	60	63
OM-F10-080-060	80	60
OM-F10-080-076	80	76
OM-F10-100-080	100	80
OM-F10-100-090	100	90
OM-F10-100-102	100	102
OM-F10-120-100	120	100
OM-F10-120-125	120	125

Reducing plug with hose tail		
<b>F.11</b>		
code	size	hose I.D. [mm]
OM-F11-060-050	60	50
OM-F11-060-063	60	63
OM-F11-080-060	80	60
OM-F11-080-076	80	76
OM-F11-100-080	100	80
OM-F11-100-090	100	90
OM-F11-100-102	100	102
OM-F11-120-100	120	100
OM-F11-120-125	120	125