

INDUSTRIAL HOSES - air-conditioning

Hand crimper for air-conditioning hoses



Crimping machines designed to assemble fittings on standard rubber hoses for air-conditioning systems in diameters: 5/16" (8 mm), 13/32" (10.3 mm), 1/2" (12.7 mm), 5/8" (16 mm). Using appropriate die sets, one can assemble fittings on standard hoses and hoses with reduced outside diameter. Heads of the crimping machines allow the hose to be pulled through them. This assembly solution makes crimping of the angular fittings particularly easy. TNT 250 - six dies crimp. Depending on a version crimping is performed manually with the help of a special key, by hydraulic pump that is manually or pneumatically operated. TNT 8 - eight dies crimp. Depending on a version crimping is performed by a simple electric drill, by hydraulic pump that is manually or pneumatically operated.

code	description
PF-TNT250-B	Hand crimper, 6 die sets for standard and reduced O.D. hoses, lubricant, plastic calliper, tool case.
PF-TNT250-P	Hand crimper with manually operated hydraulic pump, 6 die sets for standard and reduced O.D. hoses, lubricant, plastic calliper, tool case.
PF-APT100	Pneumatically operated hydraulic pump (700 bar) - TNT 250.
PF-MPT100	Manually operated hydraulic pump.
PF-UHT100	Hydraulic actuator 5.6 T with 1.8 m hose (700 bar).
PF-HCT100	Hydraulic actuator 5.6 T.
PF-HET100	1.8 m hose (700 bar).
PF-TNT8-MPT100MOSI	Hand crimper with hydraulic pump operated by an electrical drill, 6 die sets for standard and reduced O.D. hoses, tool case.
PF-TNT8-MPT10032SE	Hand crimper with manually operated hydraulic pump, 6 die sets for standard and reduced O.D. hoses, tool case.
PF-TNT8-UHTM	Hand crimper with hydraulic actuator with 1.8 m hose, 6 die sets for standard and reduced O.D. hoses, tool case.
PF-APT100-TNT8	Pneumatically operated hydraulic pump (300 bar) - TNT 8.



PF-TNT250-P



PF-APT100



PF-TNT8-MPT100MOSI



PF-TNT8-MPT10032SE