

MACHINES AND ACCESSORIES - hose reels

REELCRAFT spring retractable reels



S series

Material: Polypropylene (black)
Working temp.: Up to +65°C
 (SHA3850 OLP version up to +85°C)

A general purpose hose reel, wall-mounted. Available with a hose and swivel mounting brackets as a standard. Widely used in car workshops, agriculture, gardening, industrial plants. A wire stand (RC-SG261398) to place the hose reel on the floor available on request.

Advantages: Light weight, corrosion resistant components.

code	usage	hose length [m]	hose I.D. [inch]	working pressure [bar]	weight [kg]	connection inlet / outlet [NPT fem. / NPT male]	
RC-SGA3665OLP	air / water	20	3/8	16	11.00	3/8"	3/8"
RC-SGA3850OLP	air / water	15	1/2	16	10.00	1/2"	1/2"
RC-SHA3850OLP	hot water	15	1/2	17	10.00	1/2"	1/2"



LC series

Material: Powder coated steel
Working temp.: Up to +65°C

A hose reel intended for water and air; wall-mounted. A guide arm adjustable to five different positions allows to mount the reel in the most comfortable position. Widely used in car workshops, repair shops, petrol stations, gardening, paint shops, etc.
 Advantages: easy installation, very long service life of a retraction spring.

code	usage	hose length [m]	hose I.D. [inch]	working pressure [bar]	weight [kg]	connection inlet / outlet [BSPT fem. / BSPT male]	
RC-LC650-OLP-70	with hose	15	3/8	21	17.00	1/4"	1/4"
RC-LC670-OLP-70	with hose	21	3/8	21	20.00	1/4"	1/4"
RC-LC850-OLP-70	with hose	15	1/2	21	19.00	1/2"	1/2"
RC-LC870-OLP-70	with hose	21	1/2	21	22.00	1/2"	1/2"
OLS version - stainless steel							
RC-LC607-OLS-70-S	without hose	21	3/8	21	16.00	1/4"	1/4"
RC-LC807-OLS-70-S	without hose	21	1/2	21	16.00	1/2"	1/2"