







INDUSTRIAL HOSES - brake

Fittings for PTFE brake hoses DN3 - reusable

description	code	material	thread size	L [mm]	L1 [mm]	L2 [mm]	CH 1 [mm]	CH 2 [mm]	CH 3 [mm]
Straight female (with a nut) 	RK-FAGR-0N	chromium plated steel	M10x1.25	40	-	-	14	12	11
	RK-FAGR-1N		M10x1	40	-	-	14	12	11
	RK-FAGR-2N		3/8"-24	40	-	-	14	12	11
45° female elbow (with a nut) 	RK-FAG45R-0N	chromium plated steel	M10x1.25	22	55	-	14	12	11
	RK-FAG45R-1N		M10x1	22	55	-	14	12	11
	RK-FAG45R-2N		3/8"-24	22	55	-	14	12	11
90° female elbow (with a nut) 	RK-FAG90R-0N	chromium plated steel	M10x1.25	37	43	-	14	12	11
	RK-FAG90R-1N		M10x1	37	43	-	14	12	11
	RK-FAG90R-2N		3/8"-24	37	43	-	14	12	11
Straight male (with a nut) 	RK-MAGR-0N	chromium plated steel	M10x1.25	45	16	-	10	11	11
	RK-MAGR-1N		M10x1	45	16	-	10	11	11
	RK-MAGR-2N		3/8"-24	45	16	-	10	11	11
45° male elbow (with a nut) 	RK-MAG45R-0N	chromium plated steel	M10x1.25	22	50	16	10	11	11
	RK-MAG45R-1N		M10x1	22	50	16	10	11	11
	RK-MAG45R-2N		3/8"-24	22	50	16	10	11	11
90° male elbow (with a nut) 	RK-MAG90R-0N	chromium plated steel	M10x1.25	40	37	16	10	11	11
	RK-MAG90R-1N		M10x1	40	37	16	10	11	11
	RK-MAG90R-2N		3/8"-24	40	37	16	10	11	11