


# CLEANING AND WASHING - high pressure

## Accessories for high pressure water spray guns

picture	code	connection inlet / outlet	length [mm]	material	description
	RM-200085220	M22x1.5 male	600	galv. steel	ST-85 adjustable lance. Bending angle: from 20° to 140° Work. press.: 210 bar. Work. temp.: +150°C.
	RM-200085270	1/4" NPT female	600	st. steel	
	RM-200085710	1/4" BSP female 1/4" NPT female	850	galv. steel	
	RM-200085700		1000	galv. steel	
	RM-200085750		1500	galv. steel	
	RM-200085810		850	st. steel	
	RM-200085800		1000	st. steel	
	RM-200085850		1500	st. steel	

picture	code	calibration	connection	description
	RM-200357530	03	1/4" BSP female	Rotary head for MT1, MT2, MT6 lances. Working press.: 100 + 250 bar. Working temp.: +100°C.
	RM-200357535	035		
	RM-200357540	04		
	RM-200357545	045		
	RM-200357550	05		
	RM-200357555	055		
	RM-200357560	06		
	RM-200357565	065		
	RM-200357570	07		
	RM-200357580	08		
RM-200357510	10			
	RM-200458635	035	1/4" BSP female	Rotary head for MT1, MT2, MT6 lances. Working press.: 200 + 400 bar. Working temp.: +100°C.
	RM-200458640	04		
	RM-200458645	045		
	RM-200458650	05		
	RM-200458655	055		
	RM-200458660	06		
	RM-200458665	065		
	RM-200458670	07		
	RM-200458680	08		
	RM-200458690	09		
RM-200458610	10			
	MH-160152	030	1/4" BSP female	Rotary head for MT1, MT2, MT3, MT6 lances. Working press.: 200 + 400 bar. Working temp.: +100°C.
	MH-160153	035		
	MH-160192	040		
	MH-160154	045		
	MH-160155	050		
	MH-160156	055		
	MH-160193	060		
	MH-160194	065		
	MH-160195	070		
	MH-160196	075		
	MH-160197	080		
	MH-160198	090		
MH-160157	10			
	MH-160018	**	1/4" BSP female	DUALJET adjustable head for MT1, MT2, MT6 lances. Adjustable spray angle and pressure (low or high). Working press.: 220 bar. Working temp.: +150°C. ** - head without nozzle
	MH-160009	03		
	MH-160010	035		
	MH-160011	045		
	MH-160012	05		
	MH-160013	055		
	MH-160014	065		
	MH-160015	075		
MH-160016	08			