










INDUSTRIAL FITTINGS - couplings

Threaded couplings - DN adapters

Material: SS (AISI 316Ti), Ms (brass), Al (aluminium)

Adapter with male thread at both ends.

picture	code	thread	material	weight [kg]	pic.		
 <p>1</p>	RS-410050050120	1/2" BSP	SS	0.05	1		
	RS-410050050130		Ms	0.05	1		
	 <p>2</p>	RS-410075075120	3/4" BSP	SS	0.07	1	
		RS-410075075130		Ms	0.08	1	
		 <p>3</p>	RS-410100100120	1" BSP	SS	0.13	1
			RS-410100100130		Ms	0.13	1
 <p>4</p>	RS-410125125120	1.1/4" BSP	SS	0.16	1		
	RS-410125125130		Ms	0.16	1		
	 <p>5</p>	RS-410150150120	1.1/2" BSP	SS	0.25	1	
		RS-410150150130		Ms	0.21	2	
		 <p>6</p>	RS-410200200120	2" BSP	SS	0.33	1
			RS-410200200130		Ms	0.39	2
RS-430200200130			Ms		0.28	4	
RS-420200200130			Ms		0.28	5	
RS-430200200140	Al		0.10		4		
RS-420200200140	Al		0.09		5		
 <p>4</p>	RS-410250250120	2.1/2" BSP	SS	0.55	1		
	RS-410250250130		Ms	0.77	1		
	RS-430250250130		Ms	0.43	4		
	RS-420250250130		Ms	0.37	5		
	RS-430250250140		Al	0.12	4		
	RS-420250250140		Al	0.10	5		
 <p>5</p>	RS-410300300120	3" BSP	SS	0.62	1		
	RS-410300300130		Ms	0.67	2		
	RS-430300300130		Ms	0.55	4		
	RS-420300300130		Ms	0.56	5		
	RS-430300300140		Al	0.19	4		
	RS-420300300140		Al	0.20	5		
 <p>6</p>	RS-410400400120	4" BSP	SS	1.05	3		
	RS-410400400130		Ms	1.70	2		
	RS-430400400130		Ms	1.05	4		
	RS-420400400130		Ms	0.85	5		
	RS-430400400140		Al	0.34	4		
	RS-420400400140		Al	0.33	5		
	RS-410550550530	5.1/2" DIN 11	Ms	5.15	6		
	RS-410550550540		Al	1.80	6		