

INDUSTRIAL FITTINGS - valves

Gate valves



Gate valve 2000 type

Body material: Brass
Gate material: Brass
Knob material: Carbon steel
Stem seal: EPDM
Connection: BSP female thread
Working temp.: From -10°C up to +80°C

A general purpose gate valve designed for industry installations. The valve can be used to control or throttle flow. Working pressure depends on working temperature.

code	flow diameter [mm]	length [mm]	thread size [inch]	working pressure [bar]
RV-2000-06	13	33	1/4	10
RV-2000-10	13	33	3/8	10
RV-2000-13	14	35	1/2	10
RV-2000-19	15	40	3/4	10
RV-2000-25	19	43	1	10
RV-2000-32	27	48	1.1/4	10
RV-2000-38	33	53	1.1/2	10
RV-2000-50	45	58	2	10



Gate valve 2010 type

Body material: Brass
Gate material: Brass
Knob material: Carbon steel
Stem seal: EPDM
Connection: BSP female thread
Working temp.: From -10°C up to +90°C

A general purpose gate valve designed for industry installations. The valve is can be used to control or throttle flow. Working pressure depends on working temperature.

code	flow diameter [mm]	length [mm]	thread size [inch]	working pressure [bar]
RV-2010-013	15	38	1/2	16
RV-2010-019	19	44	3/4	16
RV-2010-025	24	48	1	16
RV-2010-032	32	51	1.1/4	16
RV-2010-038	37	58	1.1/2	16
RV-2010-050	47	60	2	16
RV-2010-065	60	64	2.1/2	16
RV-2010-075	69	74	3	16
RV-2010-090	83	82	3.1/2	16
RV-2010-100	89	86	4	16
RV-2010-125	117	95	5	10
RV-2010-150	143	105	6	10