

# INDUSTRIAL FITTINGS - valves

## Check valves and filters



### Foot valve 2350 type

**Body material:** Brass  
**Obturator:** Brass  
**Sealing:** NBR  
**Connection:** BSP female thread  
**Working temp.:** From -10°C up to +90°C

A general purpose foot valve designed for industrial installations. The valve must be mounted according to the flow direction marked on its body. Working pressure depends on working temperature.

| code        | thread size [inch] | length [mm] | working pressure [bar] |
|-------------|--------------------|-------------|------------------------|
| RV-2350-019 | 3/4                | 70          | 10                     |
| RV-2350-025 | 1                  | 82          | 10                     |
| RV-2350-032 | 1.1/4              | 95          | 8                      |
| RV-2350-038 | 1.1/2              | 103         | 8                      |
| RV-2350-050 | 2                  | 121         | 8                      |
| RV-2350-065 | 2.1/2              | 137         | 6                      |
| RV-2350-075 | 3                  | 173         | 6                      |
| RV-2350-100 | 4                  | 199         | 6                      |
| RV-2350-125 | 5                  | 239         | 6                      |
| RV-2350-150 | 6                  | 267         | 6                      |



### Swing check valve 2251 type

**Body material:** Brass (up to 4"), bronze (5" and 6")  
**Obturator:** Brass  
**Connection:** BSP female thread  
**Working temp.:** From -10°C up to +90°C

A general purpose swing check valve designed for industrial installations. The valve must be mounted according to the flow direction marked on its body. Working pressure depends on working temperature.

| code        | thread size [inch] | length [mm] | working pressure [bar] |
|-------------|--------------------|-------------|------------------------|
| RV-2251-013 | 1/2                | 47          | 16                     |
| RV-2251-019 | 3/4                | 54          | 16                     |
| RV-2251-025 | 1                  | 64          | 16                     |
| RV-2251-032 | 1.1/4              | 76          | 16                     |
| RV-2251-038 | 1.1/2              | 83          | 16                     |
| RV-2251-050 | 2                  | 98          | 16                     |
| RV-2251-065 | 2.1/2              | 116         | 16                     |
| RV-2251-075 | 3                  | 135         | 16                     |
| RV-2251-100 | 4                  | 164         | 10                     |
| RV-2251-125 | 5                  | 206         | 10                     |
| RV-2251-150 | 6                  | 235         | 10                     |