

INDUSTRIAL FITTINGS - valves

Check valves and filters



Spring check valve 2280 type

Body material:	Brass
Spring material:	AISI 302 steel
Disc material:	POM
Sealing:	NBR
Connection:	BSP female thread
Min. opening press:	0.02 bar - 3/8" ÷ 2.1/2"
	0.1 bar - 3" ÷ 4"
Working temp.:	From -10°C up to +90°C

A general purpose spring check valve designed for industrial installations. It can be mounted in any position. However, the valve must be mounted according to the flow direction marked on its body. Working pressure depends on working temperature.

code	thread size [inch]	length [mm]	working pressure [bar]
RV-2280-010	3/8	45	16
RV-2280-013	1/2	48	16
RV-2280-019	3/4	53	16
RV-2280-025	1	59	16
RV-2280-032	1.1/4	66	10
RV-2280-038	1.1/2	71	10
RV-2280-050	2	80	10
RV-2280-065	2.1/2	93	8
RV-2280-075	3	104	8
RV-2280-100	4	119	8



Spring check valve 2281 type

Body material:	Brass
Spring material:	AISI 302 steel
Disc material:	Brass
Sealing:	Viton
Connection:	BSP female thread
Min. opening press:	0.02 bar - 3/8" ÷ 2.1/2"
	0.1 bar - 3" ÷ 4"
Working temp.:	From -10°C up to +90°C

A general purpose spring check valve designed for industrial installations. It can be mounted in any position. However, the valve must be mounted according to the flow direction marked on its body. Working pressure depends on working temperature.

code	thread size [inch]	length [mm]	working pressure [bar]
RV-2281-013	1/2	48	35
RV-2281-019	3/4	53	35
RV-2281-025	1	59	35
RV-2281-032	1.1/4	66	25
RV-2281-038	1.1/2	71	25
RV-2281-050	2	80	25
RV-2281-065	2.1/2	93	12
RV-2281-075	3	104	12
RV-2281-100	4	119	12