


INDUSTRIAL FITTINGS - fittings, connectors


Brass connectors - RV type


Material: Brass


Working temp.: From -10°C up to +100°C


90° elbow BSP female		
		
3400		
code	size	thread size [inch]
RV-3400-04	8	1/4
RV-3400-06	10	3/8
RV-3400-08	15	1/2
RV-3400-12	20	3/4
RV-3400-16	25	1
RV-3400-20	32	1.1/4
RV-3400-24	40	1.1/2
RV-3400-32	50	2

90° elbow BSP female / male		
		
3401		
code	size	thread size [inch]
RV-3401-04	8	1/4
RV-3401-06	10	3/8
RV-3401-08	15	1/2
RV-3401-12	20	3/4
RV-3401-16	25	1
RV-3401-20	32	1.1/4
RV-3401-24	40	1.1/2
RV-3401-32	50	2

Adapter BSP female		
		
3410		
code	size	thread size [inch]
RV-3410-04	8	1/4
RV-3410-06	10	3/8
RV-3410-08	15	1/2
RV-3410-12	20	3/4
RV-3410-16	25	1
RV-3410-20	32	1.1/4
RV-3410-24	40	1.1/2
RV-3410-32	50	2

Tee connection BSP female		
		
3420		
code	size	thread size [inch]
RV-3420-04	8	1/4
RV-3420-06	10	3/8
RV-3420-08	15	1/2
RV-3420-12	20	3/4
RV-3420-16	25	1
RV-3420-20	32	1.1/4
RV-3420-24	40	1.1/2
RV-3420-32	50	2

Nipple BSP male		
		
3430		
code	size	thread size [inch]
RV-3430-04	8	1/4
RV-3430-06	10	3/8
RV-3430-08	15	1/2
RV-3430-12	20	3/4
RV-3430-16	25	1
RV-3430-20	32	1.1/4
RV-3430-24	40	1.1/2
RV-3430-32	50	2

Reduction nipple BSP male			
			
3430			
code	size	thread size [inch]	thread size [inch]
RV-3430-04-06	8	1/4	3/8
RV-3430-06-08	10	3/8	1/2
RV-3430-08-12	15	1/2	3/4
RV-3430-12-16	20	3/4	1
RV-3430-16-20	25	1	1.1/4
RV-3430-20-24	32	1.1/4	1.1/2
RV-3430-24-32	40	1.1/2	2
RV-3430-32-40	50	2	2.1/2