

## INDUSTRIAL FITTINGS - valves



### Ball valve 4174/4334 type

**Body material:** Nickel-plated brass  
**Ball material:** Chrome-plated brass  
**Handle material:** Aluminium  
**Ball seal:** PTFE  
**Stem seal:** NBR  
**Working temp.:** From -20°C up to +110°C

A general purpose ball valve designed for industrial installations. Used for air, gases, water, steam, chemicals, petrochemical products, etc. Working pressure depends on working temperature.

code	flow diameter [mm]	length [mm]	thread size [inch]	working pressure [bar]
4174 type (2 x BSP female thread)				
RV-4174-06	8	38	1/4	40
RV-4174-10	10	42	3/8	40
RV-4174-13	14.5	48	1/2	40
RV-4174-19	19	57	3/4	32
RV-4174-25	24	69	1	32
4334 type (BSP male / female thread)				
RV-4334-06	8	45	1/4	40
RV-4334-10	10	48	3/8	40
RV-4334-13	14.5	55	1/2	40
RV-4334-19	19	65	3/4	32
RV-4334-25	24	77	1	32



### Ball valve 4194/4354/4424 type

**Body material:** Nickel-plated brass  
**Ball material:** Chrome-plated brass  
**Ball seal:** PTFE  
**Stem seal:** FKM+NBR  
**Working temp.:** From -20°C up to +150°C

A general purpose ball valve designed for industrial installations. Used for air, gases, water, steam, chemicals, petrochemical products, etc. Working pressure depends on working temperature.

code	flow diameter [mm]	length [mm]	thread size [inch]	working pressure [bar]
4194 type (2 x BSP female thread)				
RV-4194-06	10	45	1/4	64
RV-4194-10	10	45	3/8	64
RV-4194-13	15	59	1/2	64
RV-4194-19	20	69	3/4	40
RV-4194-25	25	83	1	40
4354 type (BSPT male / BSP female thread)				
RV-4354-10	10	52	3/8	64
RV-4354-13	15	66	1/2	64
RV-4354-19	20	76	3/4	40
RV-4354-25	25	91	1	40
4424 type (2 x BSPT male thread)				
RV-4424-13	15	71	1/2	64
RV-4424-19	20	82	3/4	40
RV-4424-25	25	97.5	1	40