

INDUSTRIAL FITTINGS - valves

Globe valves



Globe valve 2028 type

Body material: AISI 316 steel
Ball material: AISI 316 steel
Handle material: Aluminium
Stem seal: PTFE
Connection: BSP female thread
Working temp.: From -20°C up to +200°C

A general purpose globe valve intended for application in industrial installations. The valve can be used to control or throttle flow. Working pressure depends on working temperature.

code	DN [mm]	thread size [inch]	working pressure [bar]
HT-2028-08	8	1/4	10
HT-2028-10	10	3/8	10
HT-2028-15	15	1/2	10
HT-2028-20	20	3/4	10
HT-2028-25	25	1	10
HT-2028-32	32	1.1/4	10
HT-2028-40	40	1.1/2	10
HT-2028-50	50	2	10

Ball valves



Ball valve 5600 type

Body material: Nickel-plated brass
Ball material: Chrome-plated brass
Handle material: Aluminium
Ball seal: PTFE
Stem seal: NBR
Working temp.: From -20°C up to +110°C

A general purpose ball valve (tap) with hose tail, intended for application in industrial installations. Suitable for water, chemicals, petrochemical products, etc. Working pressure depends on working temperature.

code	flow diameter [mm]	thread size [inch]	hose tail size [mm]	working pressure [bar]
RV-5600-10	10	3/8	15	16
RV-5600-13	10	1/2	15	16
RV-5600-19	12.5	3/4	20	16
RV-5600-25	15	1	26	16
RV-5600-32	25	1.1/4	26	16