

INDUSTRIAL PNEUMATICS - hoses



UWSB

Hose material: Flame retardant PUR polyurethane
Working temp.: From -40°C up to +70°C

Highly flexible hose resistant to abrasion, hot welding spatter and sparks. Designed for pneumatic control systems, hand tools, industrial robots, etc. Resistant to UV radiation and ageing. The hose has straight segments of 100 mm and 500 mm at the ends with BSPT male thread fittings. Shore (A) hardness 98°. Standards - UL 94 VO (external layer).

code	O.D. [mm]	I.D. [mm]	working length [m]	outside coil diameter [mm]	coil block length [mm]	working press. 20°C [bar]	fitting male thread [inch]
SH-UWSB-06-020BK	6	4	2	49	156	11	1/4
SH-UWSB-06-050BK	6	4	5	49	488	11	1/4
SH-UWSB-06-075BK	6	4	7.5	49	754	11	1/4
SH-UWSB-06-100BK	6	4	10	49	1019	11	1/4
SH-UWSB-08-020BK	8	5	2	56	175	13	1/4
SH-UWSB-08-050BK	8	5	5	56	548	13	1/4
SH-UWSB-08-075BK	8	5	7.5	56	846	13	1/4
SH-UWSB-08-100BK	8	5	10	69	896	13	1/4
SH-UWSB-10-020BK	10	6.5	2	72	160	11	1/4
SH-UWSB-10-050BK	10	6.5	5	72	500	11	1/4
SH-UWSB-10-075BK	10	6.5	7.5	72	772	11	1/4
SH-UWSB-10-100BK	10	6.5	10	82	911	11	1/4
SH-UWSB-12-020BK	12	8	2	85	159	10	3/8
SH-UWSB-12-050BK	12	8	5	85	497	10	3/8
SH-UWSB-12-075BK	12	8	7.5	85	767	10	3/8
SH-UWSB-12-100BK	12	8	10	100	859	10	3/8