



Universal hoses for fuels and oils



FUB

Hose for automotive fuels, biofuels and oils Lining:

NBR rubber

Reinforcement: textile braid



Outer layer Black synthetic rubber

Operating temp: -40°C to +100°C
externally up to +120°C

Very flexible and flexible hose for unleaded petrol and diesel for cars, trucks and tractors. Can be used in the engine compartment of trucks. Inner layer of black, smooth NBR rubber highly resistant to fuel (oil resistance: RMA class A), suitable for use with most automotive fuels (standard diesel B7 (EN590:2017), biodiesel B20, B100, standard unleaded petrol E5 (EN228:2017), E10, E85 and E100 - 100% ethanol). Reinforced with a tough textile braid for a safety factor of 4:1. Outer layer of black, smooth, high-quality synthetic rubber resistant to oil, ozone and weather. Commonly used fuel hose for motor vehicles. Compliant with SAE J30R2 and SAE J30 R6 standards.

Chemical resistance check: NBR **chemical** resistance table (pre-selection), confirmation of resistance and conditions of use by Tubes International.

index	internal diameter [mm]	external diameter [mm]	wall thickness [mm]	working pressure [bar]	Bursting pressure [bar]	bend radius [mm]	mass [kg/m]	Roll length [m]
SP-FUB-03.2	3,2	9,2	3	12	48	20	0,08	50
SP-FUB-04	4	10	3	12	48	25	0,08	50
SP-FUB-04.5	4,5	10,5	3	12	48	27	0,09	50
SP-FUB-05	5	11	3	12	48	30	0,11	50
SP-FUB-05.5	5,5	11,5	3	12	48	33	0,11	50
SP-FUB-06	6	12	3	12	48	35	0,10	50
SP-FUB-07	7	13	3	12	48	42	0,12	50
SP-FUB-07.5	7,5	13,5	3	12	48	45	0,13	50
SP-FUB-08	8	14	3	12	48	50	0,13	50
SP-FUB-09	9	15	3	12	48	55	0,14	50
SP-FUB-09.5	9,5	15,5	3	12	48	60	0,15	50
SP-FUB-10	10	16	3	12	48	60	0,16	50
SP-FUB-12	12	19	3,5	12	48	70	0,21	50

<p>FUB hose DN8 with fitted AISI 316 stainless steel end with 1/4" BSPT male thread (NM-VT123-04) clamped with AISI 304 stainless steel MINI CLIP (AB-622014).</p>	
<p>FUB hose DN8 with fitted hydraulic end with M18x1.5 female thread (TI-ZMW111-18-05) clamped with sleeve (TI-L-15-05). Galvanised steel fittings.</p>	
<p>FUB hose DN8 with fitted hydraulic end with 1/4" NPT male thread (TI-ZNZ110-04-05-SS) clamped with sleeve (TI-L-15-05-SS). Stainless steel fittings.</p>	