

INDUSTRIAL FITTINGS - couplings

Symmetrical couplings STORZ




Blank cap with lock

Material: Aluminium (Al), brass (Ms), stainless steel (SS)
Working press.: 16 bar
Seal: White NBR rubber for aluminium, black NBR rubber for brass, Viton for stainless steel

code (aluminium)	code (brass)	code (stainless steel)	size	lug dimension KA [mm]
ST-31-500066-11	ST-31-500066-30	ST-31-500066-43	52-C	66
ST-31-500081-11	-	-	65	81
ST-31-500089-11	ST-31-500089-30	-	75-B	89
ST-31-500105-11	-	-	90	105
ST-31-500115-11	-	-	100	115
ST-31-500133-11	-	-	110-A	133
ST-31-500148-11	-	-	125	148
ST-31-500160-11	-	-	150	160

(available with a universal key)



Flanged coupling

Material: Aluminium (Al), brass (Ms), stainless steel (SS)
Working press.: 16 bar
Seal: White NBR rubber for aluminium, black NBR rubber for brass, Viton for stainless steel

code (aluminium)	code (brass)	code (stainless steel)	size	lug dimension KA [mm]	flange size	D [mm]	d [mm]	n	d1 [mm]
ST-36-031025-11	ST-36-031025-30	ST-36-031025-43	25-D	31	DN 25	115	85	4	14
ST-36-066040-11*	-	-	52-C	66	DN 40	150	110	4	18
ST-36-066050-11	ST-36-066050-30	ST-36-066050-43			DN 50	165	125	4	18
ST-36-066065-11	-	-			DN 65	185	145	4	18
ST-36-066080-11	-	-			DN 80	200	160	8	18
ST-36-081050-11	-	-			65	81	DN 50	165	125
ST-36-081065-11	ST-36-081065-30	ST-36-081065-43	DN 65	185			145	4	18
ST-36-081080-11	-	-	DN 80	200			160	8	18
ST-36-089050-11	-	-	75-B	89	DN 50	165	125	4	18
ST-36-089065-11	-	-			DN 65	185	145	4	18
ST-36-089080-11	ST-36-089080-30	ST-36-089080-43			DN 80	200	160	8	18
ST-36-089100-11	-	-			DN 100	220	180	8	18
ST-36-115100-11	-	-	100	115	DN 100	220	180	8	18
ST-36-133080-11	-	-	110-A	133	DN 80	200	160	8	18
ST-36-133100-11	ST-36-133100-30	ST-36-133100-43			DN 100	220	180	8	18
ST-36-148125-11	-	ST-36-148125-43	125	148	DN 125	250	210	8	18
ST-36-160150-11	-	ST-36-160150-43	150	160	DN 150	285	240	8	22

* - galvanized steel flanges