











# HIGH PRESSURE - fittings

## NON SKIVE fittings - N type

TI-USK	SAE flange seal			
	O-ring (NBR)		flat (polyurethane)	
flange size [inch]				
	code	d x s [mm]	code	D x d x s [mm]
1/2	TI-USK110-08	18.64 x 3.53	TI-USK110-08-PU	25.40 x 17.02 x 2.79
3/4	TI-USK110-12	24.99 x 3.53	TI-USK110-12-PU	31.72 x 23.36 x 2.79
1	TI-USK110-16	32.92 x 3.53	TI-USK110-16-PU	39.62 x 31.24 x 2.79
1.1/4	TI-USK110-20	37.69 x 3.53	TI-USK110-20-PU	44.45 x 36.07 x 2.79
1.1/2	TI-USK110-24	47.22 x 3.53	TI-USK110-24-PU	53.98 x 45.34 x 2.79
2	TI-USK110-32	56.75 x 3.53	TI-USK110-32-PU	63.50 x 54.86 x 2.79

TI-N NON SKIVE		JIC UNF thread, 74° cone			
thread size [inch]	hose I.D. [inch]	AGJ	DKJ	DKJ 90	DKJ 45
		 code	 code	 code	 code
1.1/16-16	3/4	TI-NJZ110-17-12	TI-NJW110-17-12	TI-NJW210-17-12	TI-NJW310-17-12
1.5/16-12	3/4	TI-NJZ110-21-12	TI-NJW110-21-12	TI-NJW210-21-12	TI-NJW310-21-12
	1	TI-NJZ110-21-16	TI-NJW110-21-16	TI-NJW210-21-16	TI-NJW310-21-16
1.5/8-12	1	TI-NJZ110-26-16	TI-NJW110-26-16	TI-NJW210-26-16	TI-NJW310-26-16
	1.1/4	TI-NJZ110-26-20	TI-NJW110-26-20	TI-NJW210-26-20	TI-NJW310-26-20
1.7/8-12	1.1/2	TI-NJZ110-30-24	TI-NJW110-30-24	TI-NJW210-30-24	TI-NJW310-30-24
2.1/2-12	2	TI-NJZ110-40-32	TI-NJW110-40-32	TI-NJW210-40-32	TI-NJW310-40-32

TI-N NON SKIVE		ORFS UNF thread, flat sealing			
thread size [inch]	hose I.D. [inch]	AGO	DKO	DKO 90	DKO 45
		 code	 code	 code	 code
1.3/16-12	3/4	TI-NOZ110-19-12	TI-NOW110-19-12	TI-NOW210-19-12	TI-NOW310-19-12
1.7/16-12	1	TI-NOZ110-23-16	TI-NOW110-23-16	TI-NOW210-23-16	TI-NOW310-23-16
1.11/16-12	1.1/4	TI-NOZ110-27-20	TI-NOW110-27-20	TI-NOW210-27-20	TI-NOW310-27-20
2-12	1.1/2	TI-NOZ110-32-24	TI-NOW110-32-24	TI-NOW210-32-24	TI-NOW310-32-24