





**Type P fittings for UHP thermoplastic hoses (700÷ 800 bar)**

TI-P (700 ÷ 800 bar)		collets		
Hose inside diameter [inch].				
		index (galvanised steel)	index (stainless steel AISI 316L)	inner diameter of the sleeve
5/32"		TI-PSAF-025-TO	-	9.8 mm
1/4"		TI-PSAF-04-TO	TI-PSAF-04-TO-SS	15.0 mm
3/8"		TI-PSAF-06-TO	TI-PSAF-06-TO-SS	20.0 mm

TI-P (700 ÷ 800 bar)		BSP thread (BSPT), 60° taper		
		AGR	AGR-K	DKR
thread size [inch]	Hose inside diameter [inch]			
		index (galvanised steel)	index (galvanised steel)	index (galvanised steel)
1/4"	5/32"	TI-PBZ110-04-025-TO	-	TI-PBW110-04-025-TO
1/4"	1/4"	TI-PBZ110-04-04-TO*	-	TI-PBW110-04-04-TO*
3/8"		TI-PBZ110-06-04-TO*	TI-PBZ130-06-04-TO*	-
3/8"	3/8"	TI-PBZ110-06-06-TO*	-	TI-PBW110-06-06-TO*

TI-P (700 ÷ 800 bar)		metric thread, 24° taper			
		OBJECTIVE	CES	DKOL	DKOS
thread size [mm]	Hose inside diameter [inch]				
		index (galvanised steel)	index (galvanised steel)	index (galvanised steel, NBR)	index (galvanised steel, NBR)
M14x1.5	1/4"	TI-PMZ111-14-04-TO	-	TI-PMW121-14-04-TO	TI-PMW122-14-04-TO**
M16x1.5		-	-	-	TI-PMW122-16-04-TO**
M18x1.5		-	TI-PMZ112-18-04-TO*	-	TI-PMW122-18-04-TO**
M22x1.5		-	-	-	TI-PMW122-22-04-TO
M24x1.5	3/8"	-	-	-	TI-PMW122-24-04-TO
M18x1.5		TI-PMZ111-18-06-TO*	-	TI-PMW121-18-06-TO	-
M20x1.5		-	-	-	TI-PMW122-20-06-TO
M22x1.5		-	TI-PMZ112-22-06-TO*	-	TI-PMW122-22-06-TO

TI-P (700 ÷ 800 bar)		NPT thread, 60° taper AGN	NPT thread	JIC, UNF thread, 74° taper DKJ
thread size [inch]	Hose inside diameter [inch]			
		index (galvanised steel)	index (galvanised steel)	index (galvanised steel)
1/4" - 18	1/4"	TI-PNZ110-04-04-TO*	TI-PNWS110-04-04-TO*	-
3/8" - 18		TI-PNZ110-06-04-TO*	TI-PNWS110-06-04-TO*	-
7/16" - 20		-	-	TI-PJW110-07-04-TO*
1/2" - 20		-	-	TI-PJW110-08-04-TO*
9/16" - 18	3/8"	-	-	TI-PJW110-09-04-TO*
3/8" - 18		TI-PNZ110-06-06-TO*	-	-
9/16" - 18		-	-	TI-PJW110-09-06-TO*
3/4" - 16		-	-	TI-PJW110-12-06-TO*

\* - also available in AISI 316 steel (-SS at the end of the index)

\*\* - also available in AISI 316 steel, sealing (o-ring) NBR (-SS at end of index)