










Standard fittings type Z

TI-Z STANDARD		SUPER CAT collars					
		SFC		SFC 90		SFC 45	
flange size [inch]	Hose inside diameter [inch]						
		index		index		index	
3/4	3/4	TI-ZSK113-12-12	☉	TI-ZSK213-12-12	☉	TI-ZSK313-12-12	☉
	3/4	TI-ZSK113-16-12	☉	TI-ZSK213-16-12	☉	TI-ZSK313-16-12	☉
1	1	TI-ZSK113-16-16	☉	TI-ZSK213-16-16	☉	TI-ZSK313-16-16	☉
	1	TI-ZSK113-20-16	☉	TI-ZSK213-20-16	☉	TI-ZSK313-20-16	☉
1.1/4	1.1/4	TI-ZSK113-20-20	☉	TI-ZSK213-20-20	☉	TI-ZSK313-20-20	☉
	1.1/4	TI-ZSK113-24-20	☉	TI-ZSK213-24-20	☉	TI-ZSK313-24-20	☉
1.1/2	1.1/2	TI-ZSK113-24-24	☉	TI-ZSK213-24-24	☉	TI-ZSK313-24-24	☉

TI-USK	SAE flange gaskets			
	O-ring (NBR)		flat (polyurethane)	
flange size [inch]				
	index	d x s [mm]	index	D x d x s [mm]
1/2	TI-USK110-08	18,64 x 3,53	TI-USK110-08PU	25.4 x 17.0 x 2.79
3/4	TI-USK110-12	24,99 x 3,53	TI-USK110-12PU	31.7 x 23.4 x 2.79
1	TI-USK110-16	32,92 x 3,53	TI-USK110-16PU	39.6 x 31.2 x 2.79
1.1/4	TI-USK110-20	37,69 x 3,53	TI-USK110-20PU	44.4 x 36.1 x 2.79
1.1/2	TI-USK110-24	47,22 x 3,53	TI-USK110-24PU	54.0 x 45.3 x 2.79
2	TI-USK110-32	56,75 x 3,53	TI-USK110-32PU	63.5 x 54.9 x 2.79

TI-Z STANDARD		ORFS thread UNF, flat seal							
		AGO	DKO	DKO 90	DKO 45				
thread size [inch]	Hose inside diameter [inch]								
		index		index		index		index	
9/16-18	1/4	TI-ZOZ110-09-04	☉ ☉	TI-ZOW110-09-04	☉	TI-ZOW210-09-04	☉ ☉	TI-ZOW310-09-04	☉ ☉
	5/16	-		TI-ZOW110-09-05		TI-ZOW210-09-05		TI-ZOW310-09-05	
	3/8	-		TI-ZOW110-09-06		TI-ZOW210-09-06		TI-ZOW310-09-06	
11/16-16	1/4	TI-ZOZ110-11-04		TI-ZOW110-11-04	☉	TI-ZOW210-11-04	☉ ☉	TI-ZOW310-11-04	☉ ☉
	5/16	TI-ZOZ110-11-05	☉ ☉	TI-ZOW110-11-05	☉	TI-ZOW210-11-05	☉ ☉	TI-ZOW310-11-05	☉
	3/8	TI-ZOZ110-11-06	☉ ☉	TI-ZOW110-11-06	☉	TI-ZOW210-11-06	☉ ☉	TI-ZOW310-11-06	☉ ☉
13/16-16	3/8	TI-ZOZ110-13-06		TI-ZOW110-13-06	☉ ☉	TI-ZOW210-13-06	☉ ☉	TI-ZOW310-13-06	☉ ☉
	1/2	TI-ZOZ110-13-08	☉ ☉	TI-ZOW110-13-08	☉	TI-ZOW210-13-08	☉ ☉	TI-ZOW310-13-08	☉ ☉
1-14	1/2	TI-ZOZ110-16-08		TI-ZOW110-16-08	☉	TI-ZOW210-16-08	☉	TI-ZOW310-16-08	☉
	5/8	TI-ZOZ110-16-10	☉ ☉	TI-ZOW110-16-10	☉ ☉	TI-ZOW210-16-10	☉ ☉	TI-ZOW310-16-10	☉ ☉
1.3/16-12	1/2	TI-ZOZ110-19-08		TI-ZOW110-19-08	☉	-		-	
	5/8	TI-ZOZ110-19-10		TI-ZOW110-19-10	☉	TI-ZOW210-19-10		TI-ZOW310-19-10	
	3/4	TI-ZOZ110-19-12	☉ ☉	TI-ZOW110-19-12	☉	TI-ZOW210-19-12	☉ ☉	TI-ZOW310-19-12	☉
1.7/16-12	3/4	TI-ZOZ110-23-12		TI-ZOW110-23-12	☉ ☉	TI-ZOW210-23-12	☉ ☉	TI-ZOW310-23-12	☉
	1	TI-ZOZ110-23-16	☉ ☉	TI-ZOW110-23-16	☉ ☉	TI-ZOW210-23-16	☉ ☉	TI-ZOW310-23-16	☉ ☉
1.11/16-12	1.1/4	TI-ZOZ110-27-20	☉ ☉	TI-ZOW110-27-20	☉ ☉	TI-ZOW210-27-20	☉ ☉	TI-ZOW310-27-20	☉ ☉
2-12	1.1/2	TI-ZOZ110-32-24	☉ ☉	TI-ZOW110-32-24	☉ ☉	TI-ZOW210-32-24	☉ ☉	TI-ZOW310-32-24	☉ ☉

☉ - available in carbon steel with zinc-nickel plating

☉ - available in AISI 316 steel