








PUSH-ON tips (2)

photo	index (galvanised steel)	index (brass)	index (AISI 316)	thread size [inch]	Hose inside diameter [inch]
straight, BSPT male thread, sealing on thread 	TI-YBZ130-04-04	TI-YBZ130-04-04-MO	TI-YBZ130-04-04-SS	1/4"	1/4"
	TI-YBZ130-06-06	TI-YBZ130-06-06-MO	TI-YBZ130-06-06-SS	3/8"	3/8"
	TI-YBZ130-08-08	TI-YBZ130-08-08-MO	TI-YBZ130-08-08-SS	1/2"	1/2"
	TI-YBZ130-10-10	TI-YBZ130-10-10-MO	TI-YBZ130-10-10-SS	5/8"	5/8"
	TI-YBZ130-12-12	TI-YBZ130-12-12-MO	TI-YBZ130-12-SS	3/4"	3/4"
straight, metric female thread, 24°/60° cone seal (metal to metal) 	TI-YMW111-14-04	TI-YMW111-14-04-MO	TI-YMW111-14-04-SS	M14x1.5	1/4"
	TI-YMW111-16-06	TI-YMW111-16-06-MO	TI-YMW111-16-06-SS	M16x1.5	3/8"
	TI-YMW111-18-06	TI-YMW111-18-06-MO	TI-YMW111-18-06-SS	M18x1.5	3/8"
	TI-YMW111-22-08	TI-YMW111-22-08-MO	TI-YMW111-22-08-SS	M22x1.5	1/2"
	TI-YMW111-26-10	TI-YMW111-26-10-MO	TI-YMW111-26-10-SS	M26x1.5	5/8"
	TI-YMW111-30-12	TI-YMW111-30-12-MO	TI-YMW111-30-12-SS	M30x2	3/4"
90° angle, metric female thread, cone seal 24°/60° (metal to metal) 	TI-YMW211-14-04	-	TI-YMW211-14-04-SS	M14x1.5	1/4"
	TI-YMW211-16-06	-	TI-YMW211-16-06-SS	M16x1.5	3/8"
	TI-YMW211-18-06	-	TI-YMW211-18-06-SS	M18x1.5	3/8"
	TI-YMW211-22-08	-	TI-YMW211-22-08-SS	M22x1.5	1/2"
	TI-YMW211-26-10	-	TI-YMW211-26-10-SS	M26x1.5	5/8"
	TI-YMW211-30-12	-	TI-YMW211-30-12-SS	M30x2	3/4"
straight, NPT male thread, sealing on thread 	TI-YNZ110-04-04	TI-YNZ110-04-04-MO	TI-YNZ110-04-04-SS	1/4"	1/4"
	TI-YNZ110-06-06	TI-YNZ110-06-06-MO	TI-YNZ110-06-06-SS	3/8"	3/8"
	TI-YNZ110-08-08	TI-YNZ110-08-08-MO	TI-YNZ110-08-08-SS	1/2"	1/2"
	TI-YNZ110-12-12	TI-YNZ110-12-12-MO	TI-YNZ110-12-12-SS	3/4"	3/4"
	-	-	TI-YNZ110-16-16-SS	1"	1"
straight, UNF female thread, 74° cone seal (JIC) 	TI-YJW110-07-04	TI-YJW110-07-04-MO	TI-YJW110-07-04-SS	7/16"-20	1/4"
	TI-YJW110-09-06	TI-YJW110-09-06-MO	TI-YJW110-09-06-SS	9/16"-18	3/8"
	TI-YJW110-12-08	TI-YJW110-12-08-MO	TI-YJW110-12-08-SS	3/4"-16	1/2"
	TI-YJW110-14-08	TI-YJW110-14-08-MO	TI-YJW110-14-08-SS	7/8"-14	1/2"
	-	TI-YJW110-14-10-MO	TI-YJW110-14-10-SS	7/8"-14	5/8"
	TI-YJW110-17-12	TI-YJW110-17-12-MO	TI-YJW110-17-12-SS	1.1/16"-12	3/4"
	-	-	TI-YJW110-21-16-SS	1.5/16"-12	1"

Other types of PUSH-ON terminals are available on special order, including PUSH-ON terminals with a connection according to customer specifications.

 <p>3/8" BSP galvanised steel banjo tip (TI-YBB600-06-06) fitted to a 3/8" PUSH-ON hose.</p>	<p>Angled quick-connect socket for injection mould cooling with PUSH-ON hose end, fitted to PUSH-ON hose DN10 (3/8").</p> <p><i>For quick-action couplings for injection moulds, see section INDUSTRIAL FITTINGS.</i></p>	 <p>PUSH-ON (135°C)</p>
---	---	--