

Hoses for fuel and oil loading/unloading



AUSTRALIA®

Lightweight delivery hose for diesel and heating oil (up to 30% aromatics)

- Inner layer:** black NBR rubber
- Reinforcement:** synthetic cord
- Outer layer:** black synthetic rubber
- Work. temp.:** from -20°C to +70°C

Lightweight and flexible, delivery hose designed for transferring liquid petrochemical products containing up to 30% aromatic compounds (e.g. diesel oil, heating oil). Black, smooth NBR rubber inner layer. Synthetic cord reinforcement. It has a copper wire to ensure electrical continuity between the fittings of a hose assembly. The outer layer of high-quality synthetic rubber is resistant to abrasion, oil, ozone and weather conditions.

It is a very light and handy hose with soft and flexible construction. The hose comes in a variety of sizes and with different types of fittings, making it a favourite choice for light to medium duty applications.

Versions available to special order: AUSTRALIA SUPER (aromatic compounds up to 50%) and AUSTRALIA REEL (for rolling up on reels, aromatic compounds also up to 50%). See also 16 bar version: AUSTRALIA EN 1360.

Chemical resistance check: NBR chemical resistance chart (initial selection), confirmation of resistance and conditions of use by Tubes International.

code	I.D. [mm]	O.D. [mm]	wall thickness [mm]	working pressure [bar]	burst pressure [bar]	weight [kg/m]	coil length [m]
IV-AUSTRALIA-010	10	17	3.5	10	30	0.19	60 / 120
IV-AUSTRALIA-013	13	20	3.5	10	30	0.24	60 / 120
IV-AUSTRALIA-019	19	27	4	10	30	0.36	60 / 120
IV-AUSTRALIA-022	22	31	4.5	10	30	0.48	60 / 120
IV-AUSTRALIA-025	25	35	5	10	30	0.62	60 / 120
IV-AUSTRALIA-028	28	38	5	10	30	0.68	60 / 120
IV-AUSTRALIA-032	32	42	5	10	30	0.76	60 / 120
IV-AUSTRALIA-035	35	45	5	10	30	0.76	60 / 120
IV-AUSTRALIA-038	38	47	4.5	10	30	0.74	60 / 120
IV-AUSTRALIA-040	40	50	5	10	30	0.85	60 / 120
IV-AUSTRALIA-045	45	55	5	10	30	0.95	60 / 120
IV-AUSTRALIA-051	51	61	5	10	30	1.06	60 / 120
IV-AUSTRALIA-060	60	73	6.5	10	30	1.72	60 / 120
IV-AUSTRALIA-063	63.5	74	5.25	10	30	1.39	60 / 120
IV-AUSTRALIA-076	76	89	6.5	10	30	2.03	60 / 120
IV-AUSTRALIA-090	90	105	7.5	10	30	2.70	60 / 120

Note: colour marked codes - used most often.



AUSTRALIA hose DN10 with NPT 1/2" male thread hydraulic fitting (TI-ZNZ110-08-06-CN) crimped with a ferrule (TI-L19-06).

AUSTRALIA hose DN51 with brass CAMLOCK coupling (AC-C-200-B) assembled with two worm drive clamps in stainless steel.