






INDUSTRIAL FITTINGS - couplings

TW couplings (EN ISO 14420-6, DIN 28450)

picture	code	size	material	weight [kg]
VB plug (supplied without chain) 	TW-VB-050-SSR	VB 50	AISI 316	0.31
	TW-VB-050-SSE		AISI 316 / E-CTFE	-
	TW-VB-050-MSR		brass	0.32
	TW-VB-050-ALR		aluminium	0.13
	TW-VB-080-SSR	VB 80	AISI 316	0.76
	TW-VB-080-SSE		AISI 316 / E-CTFE	-
	TW-VB-080-MSR		brass	0.85
	TW-VB-080-ALR		aluminium	0.25
	TW-VB-100-SSR	VB 100	AISI 316	1.15
	TW-VB-100-SSE		AISI 316 / E-CTFE	-
	TW-VB-100-ALR		brass	0.44

picture	code	size	material	weight [kg]	
TWF cap seal 	TW-TWF-050-PU	TWF 2" DN50	polyurethane	0.007	
	TW-TWF-050-NBR		NBR		
	TW-TWF-050-VI		Viton	0.010	
	TW-TWF-050-HY		Hypalon	0.007	
	TW-TWF-050-PTFE		PTFE	0.011	
	TW-TWF-050-EP		EPDM	0.007	
	TW-TWF-080-PU	TWF 3" DN80	polyurethane	0.016	
	TW-TWF-080-NBR		NBR		
	TW-TWF-080-VI		Viton	0.022	
	TW-TWF-080-HY		Hypalon	0.018	
	TW-TWF-080-PTFE		PTFE	0.025	
	TW-TWF-080-EP		EPDM	0.016	
	TWO coupling seal 	TW-TWO-100-NBR	TWF 4" DN100	NBR	0.016
		TW-TWO-100-VI		Viton	0.027
TW-TWO-100-HY		Hypalon		0.020	
TW-TWO-100-PTFE		PTFE		0.026	
GSD coupling seal 	TW-GSD-050-PU	GSD 2" DN50	polyurethane	0.008	
	TW-GSD-050-NBR		NBR	0.009	
	TW-GSD-050-VI		Viton	0.012	
	TW-GSD-050-HY		Hypalon	0.011	
	TW-GSD-080-PU	GSD 3" DN80	polyurethane	0.015	
	TW-GSD-080-NBR		NBR	0.018	
	TW-GSD-080-VI		Viton	0.026	
	TW-GSD-080-HY		Hypalon	0.022	
	TW-GSD-080-BIT		vamac	0.015	
GD thread seal 	GD-050-PU	GD 2" DN50	polyurethane	0.004	
	GD-050-VI		Viton	0.003	
	GD-050-PTFE		PTFE	0.004	
	GD-050-EP		EPDM		
	GD-080-PU	GD 3" DN80	polyurethane	0.006	
	GD-080-VI		Viton		
	GD-080-PTFE		PTFE		
	GD-080-EP		EPDM		
	GD-100-PU	GD 4" DN100	polyurethane	0.009	
	GD-100-VI		Viton	0.014	
	GD-100-PTFE		PTFE	0.009	
	GD-100-EP		EPDM		