

MACHINES AND ACCESSORIES - protection and sealing

Threadlockers



code	volume [ml]	description
WE-AN30-260-P-020	20	Thread-locking fluid - for use in passive materials without activating agent, medium viscosity, high durability - difficult disassembly. Working temp.: from -60°C up to +180°C. P - type pen container
WE-AN30-260-P-050	50	

Cyanoacrylic glues



code	package capacity	description
WE-VA100-P-003	3 g	Medium viscosity, fast hardening, general purpose glue for plastics, rubber and metals in different combinations of the three. P - type pen container, T - tube.
WE-VA100-T-012	12 g	
WE-VA-AS	150 ml	Activating agent for porous surfaces as well as for hardening acceleration of WE-VA glues.

Metal sprays



code	volume [ml]	description
WE-ZSN-400	400	Zinc anticorrosive coating, 70% of zinc in dry coating (99% pure), thermal resistance up to +500°C.
WE-A-100	400	Aluminium pigments of >99.5% purity, thermal resistance up to +800°C, abrasion resistant.
WE-A-400	400	Aluminium pigments of >99.5% purity, thermal resistance up to +800°C, abrasion resistant, high gloss.

Cleaning sprays



code	volume [ml]	description
WE-W44T-400	400	High quality maintenance and preservation spray used in industry and workshop applications. W44T loosens seized screw connections, dispels moisture, eliminates squeaking and creaking, cleans dirty metal surfaces, protects and cares for all tools and machines.
WE-CLEANER-S-0500	500	Degreaser for surface preparation. Cleans and degreases metals, glass, ceramics, wood. Removes old solid grease. Evaporates quickly leaving no spots on the surface.