Industrial chemicals – oils and greases (2)

	index	capacity packaging	description
 1 2 3	WE-BFS-500	500 ml (fig. 1)	BIO-FLUID medical-grade spray lubricant of high purity, free of resins and acids. Intended for cleaning and care of bare-metal surfaces, especially for the food, pharmaceutical and cosmetic industries. Holds NSF H1 approval.
	WE-AL-H-400	400 g (fig. 2)	Odourless and tasteless high-temperature grease for the food industry. For lubricating ball and plain bearings, shafts, gearboxes and gears. Consistency classifier (DIN 51818): NLGI Class 1; yellowish-white colour, resistant to temperatures from -40°C to +160°C. Holds NSF H1 approval – direct food contact.
	WE-USGMO-400	400 ml (fig. 3)	Spray grease with molybdenum disulphide (MoS2) additive. Strongly adhering and resistant to high pressures. Ensures smooth operation of machine components and protects against corrosion. Recommended, among others, for rolling and plain bearings, camshafts and splined shafts operating in harsh conditions.

	index	capacity packaging	description
	WE-AT44-400	400 ml	Dry PTFE spray lubricant for use in workshops and many other branches of industry, as well as domestic tasks. It is an effective anti-corrosion, cleaning, moisture-displacing, lubricating and protective product. Suitable for use over a wide temperature range from -50°C to +210°C. Silicone-free. Colour: yellowish.

	index	capacity packaging	description
	AZ-SILIKON	400 ml	General-purpose silicone spray lubricant (for maintenance, protection and lubrication). Suitable for use over a wide temperature range from -32°C to +177°C. Long-lasting protection against moisture and corrosion. Neutral towards paints, plastics, rubber, foam materials, wood and textiles.

	index	capacity packaging	description
	AZ-PENETRATOR	500 ml	Multifunctional industrial spray grease with a lemon scent, long life and excellent anti-corrosion properties. Excellent rust protection, cleans and refreshes, lubricates. Silicone-free.

	index	capacity packaging	description
	KM-US-45	500 ml	US-45 universal spray grease designed to protect against rust and verdigris. Protects against moisture. Gentle on rubber and plastics. Safe for use on batteries, starters, etc. Contains no silicones or resins. Working temperature: -25ºC to +50ºC.