




HIGH PRESSURE - fittings

Standard fittings - Z type

ZC-BP5		Crimp ferrule for thermoplastic hoses	
hose I.D. [inch]	ferrule I.D. [mm]		
		code	hose type
1/8	7.8	ZC-BP5-02	OL5 / VE5
5/32	8.6	ZC-BP5-025	
3/16	9.8	ZC-BP5-03	
1/4	11.1	ZC-BP5-04	
5/16	13.8	ZC-BP5-05	
3/8	15.1	ZC-BP5-06	
1/2	19.1	ZC-BP5-08	

ZC-BP7 / BP8		Crimp ferrule for thermoplastic hoses	
hose I.D. [inch]	ferrule I.D. [mm]		
		code	hose type
1/8	9	ZC-BP7-02	SAE100R7
5/32	9.3	ZC-BP7-025	
3/16	10.7	ZC-BP7-03	
1/4	12.4	ZC-BP7-04	
5/16	15.4	ZC-BP7-05	
3/8	17	ZC-BP7-06	
1/2	21.5	ZC-BP7-08	
5/8	24.2	ZC-BP7-10	
3/4	27.1	ZC-BP7-12	
1	33.1	ZC-BP7-16	
1	55.5	ZC-BP8-16	SAE100R8

MC-BX7		Crimp ferrule for thermoplastic hoses	
hose I.D. [inch]	ferrule I.D. [mm]		
		code	hose type
3/16	11.6	MC-BX7-03	SAE100R6 / R7 / R8
1/4	13.9	MC-BX7-04	
5/16	15.9	MC-BX7-05	
3/8	17.5	MC-BX7-06	
1/2	21.3	MC-BX7-08	
5/8	24.8	MC-BX7-10	
3/4	28.2	MC-BX7-12	
1	34.6	MC-BX7-16	SAE100R6 / R7
1		MC-BX8-16	SAE100R8

Note!
For thermoplastic and hydraulic rubber hoses with textile braid, properly selected ferrules of L type can be used (see "INDUSTRIAL FITTINGS - clips, clamps, ferrules").