Covers

GT 35

Material: polyester
Temp. range: -40ºC to +100ºC

Sleeve made of very dense polyester fabric. Intended to protect single hoses or bundles of hydraulic and pneumatic lines. Offers good mechanical resistance and resistance to oils and organic products. Protects the hose and shields the operator from oil spray in the event of hose burst.

index	inner diameter [mm]	width [mm]	weight [kg/m]	roll standard [m]
ZC-GT-035	20	35	0,027	100
ZC-GT-040	22	40	0,032	100
ZC-GT-045	25	45	0,034	100
ZC-GT-050	28	50	0,038	100
ZC-GT-055	32	55	0,042	100
ZC-GT-060	35	60	0,045	100
ZC-GT-065	38	65	0,048	100
ZC-GT-080	45	80	0,060	100
ZC-GT-090	50	90	0,065	100
ZC-GT-120	70	120	0,096	100
ZC-GT-150	90	150	0,112	100

GPVC

Material: PVC
Temp. range: -15ºC to +70ºC

Sleeve made of PVC. Intended to protect single hoses or bundles of hydraulic and pneumatic lines. Protects the hose and shields the operator from oil spray in the event of hose burst.

index	inner diameter [mm]	wall thickness [mm]	weight [kg/m]	roll standard [m]
ZC-GPVC-10	10	0,5	0,026	125
ZC-GPVC-16	16	0,5	0,039	100
ZC-GPVC-20	20	0,6	0,058	100
ZC-GPVC-22	22	0,6	0,063	100
ZC-GPVC-25	25	0,6	0,072	100
ZC-GPVC-25S	25	1,5	0,151	100
ZC-GPVC-28	28	0,6	0,082	100
ZC-GPVC-30	30	0,6	0,087	100
ZC-GPVC-30S	30	1,5	0,180	100
ZC-GPVC-33	33	0,7	0,104	50
ZC-GPVC-33S	33	1,5	0,197	50
ZC-GPVC-38	38	0,7	0,135	50
ZC-GPVC-38S	38	1,5	0,225	50
ZC-GPVC-40	40	0,7	0,141	50
ZC-GPVC-45	45	0,7	0,144	50
ZC-GPVC-50	50	0,7	0,167	50
ZC-GPVC-55	55	0,7	0,184	50